



Endace DAG 8.1SX

Endace's DAG™ 8.1SX is a high-performance, single-port data capture card, designed for use in appliances for monitoring and capturing network traffic at high-speed in SONET/SDH or 10GbE environments.

The DAG 8.1SX is ideally suited for use in network performance monitoring, security analytics, data archival and latency measurement applications in large, complex, network environments where 100% packet capture is critical.

Based on PCI Express (PCIe) 1.1 x8, the DAG 8.1SX delivers full line rate data capture regardless of packet size, with captured packets transferred direct to host memory via direct memory access (DMA). This removes interrupt overhead from the host CPU and frees up CPU cycles for analysis or other tasks.

In addition to interrupt free and zero copy packet capture, the DAG 8.1SX provides extremely flexible memory allocation and powerful on-card, rule-based filtering, duplication and steering (directing packets to specific streams). This makes analyzing captured traffic simpler and quicker, enabling more powerful analysis and further reducing load on the host CPU.

The DAG 8.1SX is designed for concatenated OC-192 or SDH STM64 and supports Packet over SONET (PoS) and RAW SONET frame capture.

If dual port or wire-speed SONET de-channelization is a requirement Endace's DAG 9.2SX2 comes with two ports and supports sophisticated, hardware-based, de-channelization of SONET OC192 and STM64 down to OC3/STM1 in any channelization hierarchy while extracting PoS and ATM mapping or just the raw payload.

Captured traffic is available in industry-standard packet capture formats (PCAP) making it easy to use in the applications you choose for monitoring and analysis.

Multiple Endace DAG cards can be combined in a single appliance, enabling high-density deployment, saving rack-space, and further reducing the total cost-of-ownership.

Endace's DAG cards are engineered to ensure long life and reliability. They are trusted by customers around the world to deliver proven 100% accurate capture and low cost-of-ownership with best-in-class performance.

DAG 8.1SX AT A GLANCE

- 1x XFP monitoring port configurable for SONET OC192, SDH STM64, 10GbE LAN or WAN-PHY links
- Hardware time-stamping with synchronization from host or external time reference via a dedicated time sync port
- x8 PCIe 1.1 based card
- Linux, FreeBSD and Windows drivers

BENEFITS

Accurate

- 100% packet capture at full line rate for all packet sizes from 64 Bytes to 9600 Bytes
- Nanosecond-level time-stamping accuracy on every packet

Powerful

- Supports up to 64 classification rules for onboard filtering, duplication and steering of captured traffic in hardware at full line rate
- Relative timed replay enables precise reproduction of traffic as captured for testing, performance measurement and other purposes

Flexible

- Supports up to 32 capture streams for load balancing in multi-core host architecture
- Full packet capture or set length capture configurable for every capture stream
- Compatible with standard server architecture using x8 PCIe 1.1 bus technology

Reliable

- Engineered for high-reliability and extended mean time between failure (MTBF) rates
- Zero-fan cooling reduces failure points

We recommend the DAG 9.2SX2, 10X2-S or 10X2-P for incorporating in new designs.

DAG 8.1SX – Technical Specifications

Monitoring interfaces	1x XFP transceiver
Network type	IEEE 802.3ae LAN IEEE 802.3ae WAN SONET OC192c SDH STM64 VC4-64c
Packet encapsulations	Ethernet Packet over SONET [PoS] Raw Frames
Hardware packet processing	Enhanced Packet Processing v2
Time synchronization	External: RJ45 connector for RS-422 PPS and IRIG-B signal from GPS, CDMA or TDS Internal: Host PC clock Other DAG cards
Packet timestamping	7.5ns
PCI interface	x8 lane PCIe 1.1
Operating system supported	Endace software is supported on Linux, FreeBSD and Windows
Power requirements	Less than 20W
Operating temperature	0 to 55°C (32 to 131°F)
Airflow requirements	200 LFM (@50°C Ambient)
Operating humidity	5 to 95% non condensing
Physical dimensions	Half Height, Half Length Height: 64.25mm (2.53") Length: 167.5mm (6.6")

Companion Products

Transceivers

10GBase-SR optical XFP transceiver, 850nm Multi-mode with LC connectors	TXR-10G-850-MM
10GBase-LR optical XFP transceiver, 1310nm Single-mode with LC connectors	TXR-10G-1310-SM
10GBase-ER optical (40Km) XFP transceiver, 1550nm Single-mode with LC connectors	TXR-10G-1550-SM
10GBase-ER optical high sensitivity (80Km) XFP transceiver, 1550nm Single-mode with LC connectors	TXR-10G-1550-SM-HS

Time Measurement Accessories

Trimble Acutime™ Gold GPS receiver	GPS-2
Endace 2-port Time Distribution Server, accepts serial input from GPS/CDMA sources	TDS-2
Endace 6-port expansion module for TDS-2, shares common reference time source	TDS-6
Endace 24-port Time Distribution Server, accepts serial input from GPS/CDMA sources	TDS-24



This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the Federal Communications Commission [FCC] Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction document, may cause harmful interference to radio communications.

Endace™, the Endace logo and DAG™ are registered trademarks in New Zealand and/or other countries of Endace Technology Limited. Other trademarks used may be the property of their respective holders. Use of the Endace products described in this document is subject to the Endace Terms of Trade and the Endace End User License Agreement (EULA).

For more information on the Endace portfolio of products, visit: endace.com/products

For further information, email: info@endace.com